Product information
Multi-Disc Clutch Oil

PI 29/08/18/2026

Description
High performance gear oil specially developed for Haldex all-wheel drive, Quattro and 4motion drives. Provides excellent viscosity and shear stability as well as outstanding friction coefficient under all operating conditions. Protects reliably against wear, foaming and corrosion. Ensures optimum power transmission on all-wheel drive vehicles.



Properties
- outstanding corrosion protection
- excellent wear resistance
- excellent shear stability
- optimum friction coefficient under all operating conditions
- reliable protection against foaming
- extremely high viscosity index

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:
GM • Opel • Volvo • VW G 052 175 (TL 52175) • VW G 055 175 (TL 52175-X) • VW G 060 175 (TL 52175-Y)

Technical data

Density at 59 °F	0,85 g/cm³ DIN 51757
Viscosity at 104 °F	27,5 mm²/s ASTM D 7042-04
Viscosity at 212°F	5,7 mm²/s ASTM D 7042-04
Viscosity index	155 DIN ISO 2909
Pour point	-76 °F DIN ISO 3016
Flash point	446 °F DIN ISO 2592
Color / appearance	yellowish
Shelf life in original sealed container	36 months

Areas of application
For all-wheel drive systems with Haldex coupling where a fluid according to current specifications is required or recommended to use.

⚠ WARNING: This product can expose you to chemicals including methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Application
Observe the manufacturers instructions! Not suitable for vehicles requiring VW G 065 175. Shake well before use.

Available pack sizes

1 l Can plastic	22194 CAEN-CAFR-USEN

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com