

Molygen New Generation SAE 0W-16

Description

Fully synthetic, extreme low viscosity LIQUI MOLY specialty with a unique additive technology. The powerful MFC (Molecular Friction Control) technology prevents formation of deposits while simultaneously reducing frictional losses. The synergetic effect provides optimum wear protection even under tough operating conditions. Improved fuel consumption and increased engine life are some of the end results. Ideally suited for engines with direct injection (GDI) and turbochargers. The oils fluorescent green color is typical for the MFC formulation.

Properties

- smooth engine running
- optimum oil pressure under all operating conditions
- long engine service life
- reduces pollutant emissions
- ideal with turbochargers and catalytic converters
- excellent wear protection
- high lubrication reliability
- instant lubrication after cold start
- optimum stability to aging
- outstanding engine cleanliness
- excellent low temperature behavior
- reduces fuel consumption
- miscible with all commercially available motor oils

Specifications / Approvals

API SP • ILSAC GF-6B

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

Honda • Hyundai • Lexus • Suzuki • Toyota

Technical data

SAE class (engine oils)	0W-16 SAE J 300
Density at 59 °F	0,845 g/cm ³ DIN 51757
Viscosity at 104 °F	38,0 mm ² /s ASTM D 7042-04
Viscosity at 212°F	7,2 mm ² /s ASTM D 7042-04
Viscosity at -40 °F (MRV)	< 60000 mPas ASTM D 4684
Viscosity at -31 °F (CCS)	≤ 6200 mPas ASTM D 5293
Viscosity index	155 DIN ISO 2909



Technical data

HTHS at 302 °F	≥ 2,3 mPas ASTM D 5481
Pour point	-49 °F DIN ISO 3016
Evaporation loss (Noack)	12,5 % CEC-L-40-A-93
Flash point	446 °F DIN ISO 2592
Total base number	8,3 mg KOH/g DIN ISO 3771
Sulfate ash	0,9 g/100g DIN 51575
Color / appearance	green, fluorescent

Areas of application

For Asian or American engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers.

Comment

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Application

Observe the manufacturers instructions!

Available pack sizes

1 l Canister plastic	22251 USA-AND-CANADA-EN-F
5 l Canister plastic	22252 USA-AND-CANADA-EN-F
205 l Black plate barrel	22253 USA-AND-CANADA-EN-F
1.000 l Container	22254 USA-AND-CANADA-EN-F

Our information is based on thorough research and may be considered reliable, although not

Product information

PI 4/03/27/2023



Molygen New Generation SAE 0W-16

legally binding.