Product information

PI 26/11/13/2026

Top Tec ATF 1950



Description

Fully synthetic, low viscosity automatic transmission fluid, developed to fulfill strict requirements for Mercedes-Benz 9-speed automatic transmissions (type 725.0/1). Improved formula for sustained transmission life, maximum efficiency and best transmission shift performance.

Properties

- excellent viscosity/temperature properties
- outstanding friction characteristics
- high efficiency
- very good low-temperature properties

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:

MB 236.17

Technical data

Density at 59 °F	0,845 g/cm³ DIN 51757
Viscosity at 104 °F	20,0 mm²/s ASTM D7042
Viscosity at 212°F	4,4 mm²/s ASTM D7042
Viscosity at -40 °F (Brookfield)	<= 10000 mPas ASTM D2983
Viscosity index	135 DIN ISO 2909
Pour point	-59 °F DIN ISO 3016
Flash point	392 °F DIN ISO 2592
Color / appearance	brown

Areas of application

For Mercedes-Benz 9-speed automatic transmissions where an ATF fluid meeting current product specification is required or recommended.

Application

Observe the manufacturers instructions! Optimum efficiency and product performance is only possible when the product is used undiluted.

Available pack sizes

1 l Can plastic	22034 CAEN-CAFR-USEN

Available pack sizes

20 l Canister plastic	22291 CAEN-CAFR-USEN
205 l Black plate barrel	22296 CAEN-CAFR-USEN

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com