Product information

PI 5/08/18/2026

Marine 4T Motor Oil SAE 25W-50



Description

Heavy-duty motor oil formulated with specific synthetic marine additives. Provides a stable lubricating film and best wear protection in the most extreme conditions. Maintains engine rubber seals for lowest possible oil consumption.

Properties

- outstanding corrosion protection
- ideal with turbochargers and catalytic converters
- outstanding oil film strength
- stable to aging and stable viscosity
- optimum oil pressure under all operating conditions

Specifications / Approvals

API SM • NMMA FC-W Catalyst Compatible®

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:

Mercury Marine • NMMA FC-W

Technical data

SAE class (engine oils)	25W-50 SAE J300
Density at 59 °F	0,88 g/cm³ DIN 51757
Viscosity at 104 °F	200 mm²/s ASTM D 7042-04
Viscosity at 212°F	20 mm²/s ASTM D 7042-04
Viscosity at 14 °F (CCS)	<= 13000 mPas ASTM D 5293
Viscosity index	115 DIN ISO 2909
HTHS at 302 °F	>= 3,7 mPas ASTM D 5481
Pour point	-27 °F DIN ISO 3016
Evaporation loss (Noack)	4,6 % CEC-L-40-A-93
Flash point	446 °F DIN ISO 2592
Total base number	6,9 mg KOH/g DIN ISO 3771
Sulfate ash	< 1,0 g/100g DIN 51575

Areas of application

For 4-stroke gasoline engines where a motor oil according to current product specifications is required or recommended, particularly suitable for Mercury Verado engines. Safe with or without catalytic converters and turbochargers.

⚠ WARNING: This product can expose you to chemicals including toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Application

Observe the manufacturers instructions!

Available pack sizes

1 l Canister plastic	22508 CAEN-CAFR-USEN
4 l Canister plastic	22510 CAEN-CAFR-USEN
205 l Black plate barrel	22514 CAEN-CAFR-USEN

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com