Product information

PI 20/09/24/2026

Marine Single Grade SAE 30



Description

Mineral based single grade motor oil formulated with specific marine additives. Due to a naturally high viscosity index it provides a stable lubrication film under all operating conditions. Prevents sludge formation and offers good corrosion protection. Particularly suited for use with older engine designs and transmissions.

Properties

- optimum stability to aging
- high lubrication reliability
- high wear resistance
- can be used in gasoline and diesel engines with and without turbocharger
- universal application

Specifications / Approvals

ACEA E2 • API SJ • API CF • API CF-4

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:

MAN 270 • Volvo VDS

Technical data

SAE class (engine oils)	30 SAE J300
Density at 59 °F	0,875 g/cm³ DIN 51757
Viscosity at 104 °F	90 mm²/s ASTM D 7042-04
Viscosity at 212°F	11,6 mm²/s ASTM D 7042-04
Viscosity index	115 DIN ISO 2909
Pour point	-27 °F DIN ISO 2592
Evaporation loss (Noack)	6,8 % ASTM D 5800-08 Method B
Flash point	446 °F DIN ISO 3016
Total base number	11 mg KOH/g DIN ISO 3771
Sulfate ash	1,2 g/100g DIN 51575
Color number (ASTM)	4 DIN ISO 2049

Areas of application

For 4-stroke gasoline and diesel engines as well for transmissions where a single-grade fluid according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers.

Application

Observe the manufacturers instructions!

Available pack sizes

4 l Canister plastic	22512 CAEN-CAFR-USEN
205 l Black plate barrel	22507 CAEN-CAFR-USEN

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com