

Top Tec 4400 5W-30

Description

Top Tec 4400 is a state-of-the-art, low-ash low-friction motor oil of top quality for use all year round. The combination of unconventional base oils using synthetic technology together with the latest additive technology guarantees a motor oil that provides exceptional protection against wear and reduces oil and fuel consumption while ensuring fast oil penetration of the engine. Renault requires a motor oil with this specification for various models with diesel particulate filters (DPF) to ensure the maximum service life of the DPF. Top Tec 4400 5W-30 is also ideal for use in gas-driven passenger cars (CNG/LPG).

Properties

- outstanding engine cleanliness
- tested for turbochargers and catalytic converters
- optimum oil pressure under all operating conditions
- smooth engine running
- long engine service life
- optimum stability to aging
- high shear stability
- instant lubrication after cold start
- excellent wear resistance
- ensures a long service life
- optimum effectiveness when the product is used unmixed

Specifications / Approvals

ACEA C4 • Renault RN 0720

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:

Fiat 9.55535-S4 • MB 226.51 • MB 229.51

Technical data

SAE class (engine oils)	5W-30 SAE J300
Density at 15 °C	0,85 g/cm ³ DIN 51757
Viscosity at 40 °C	70 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	12 mm ² /s ASTM D 7042-04
Viscosity at -35 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -30 °C (CCS)	≤ 6600 mPas ASTM D5293
Viscosity index	169 DIN ISO 2909



Technical data

HTHS at 150°C	≥ 3,5 mPas ASTM D5481
Pour point	-39 °C DIN ISO 3016
Evaporation loss (Noack)	9,2 % CEC-L-40-A-93
Flash point	220 °C DIN ISO 2592
Total base number	7,6 mg KOH/g DIN ISO 3771
Sulfate ash	≤ 0,5 g/100g DIN 51575
Color number (ASTM)	L3,0 DIN ISO 2049

Areas of application

Specially for the new generation of passenger car diesel engines from Renault. Suitable for turbochargers and catalytic converters.

Application

Note the operating instructions of the vehicle and engine manufacturers.

Full effectiveness can only be ensured when the product is not mixed!

Available pack sizes

1 l Canister plastic	2319 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-UK-ZH
5 l Canister plastic	2322 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-UK-ZH
20 l Canister plastic	3752 DE-EN-ES-IT-PT
20 l Bag-in-Box	21844 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH

Product information

PI 40/09/10/2026



Top Tec 4400 5W-30

Available pack sizes

60 l Black plate barrel	3753	DE-EN-ES-FR-IT-PT
205 l Black plate barrel	3754	DE-EN-ES-FR-IT-PT

Our information is based on thorough research and may be considered reliable, although not legally binding.