

## Speed Tec Diesel

### Description

Diesel fuel additive for improved combustion and consequently faster acceleration, particularly under partial load. Perfectly compatible with all conventional diesel and biodiesel fuels. Significantly improves vehicle acceleration.

### Properties

- higher performance gain
- improves acceleration
- tested for the use with catalytic converters
- better drivability
- cleans the injection system
- suitable for diesel particulate filters
- does not influence the cetane number
- contains no organometallic compounds
- reduces frictional losses

### Technical data

|                    |                      |
|--------------------|----------------------|
| Base               | Additive combination |
| Color / appearance | yellow, clear        |
| Flash point        | >63 °C               |
| Form               | flüssig, liquid      |
| Viscosity at 40 °C | <7 mm²/s             |
| Odor               | characteristic       |
| Density at 15 °C   | 0,822 g/cm³          |

### Areas of application

Added to the diesel fuel. Especially suitable for diesel engines and fast vans. For the improvement of vehicle acceleration and smooth operation.

### Application

One 250 ml can is sufficient for max. 70 liters of diesel fuel. Mix the contents of the can with the diesel fuel. Mixing also takes place automatically.

### Available pack sizes

|                        |                     |
|------------------------|---------------------|
| 250 ml Can sheet metal | 2367<br>DA-FI-NO-SV |
| 250 ml Can sheet metal | 3722<br>DE-EN-IT    |
| 250 ml Can sheet metal | 21645<br>DE-ES-PT   |

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

