

Description

Multigrade low-friction engine oil featuring the latest technology, formulated with unconventional base oils based on HC synthetic technology and advanced additives. This low-viscosity, shear-stable engine oil ensures optimal engine cleanliness, reduces friction losses in the engine, and provides excellent wear protection. This helps extend engine life.

Turbocharger and catalytic converter tested.

Especially suitable for Opel gasoline and diesel engines up to model year 2010. However, it is backward compatible and can also be used in older Opel vehicles that permit the use of an engine oil of this viscosity grade. The manufacturer's specifications must be observed when using the product in other vehicle makes and models.

Properties

- outstanding engine cleanliness
- tested for turbochargers and catalytic converters
- optimum stability to aging
- high shear stability
- instant lubrication after cold start
- high lubrication reliability

Specifications / Approvals

ACEA A3 • ACEA B4 • API SL • BMW Longlife-01 • MB-Approval 229.5 • VW 502 00 • VW 505 00

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:

Renault RN 0700 • Renault RN 0710 • Opel GM-LL-A-025 • Opel GM-LL-B-025

Technical data

Density at 15 °C	0,855 g/cm ³ DIN 51757
Viscosity at 40 °C	72,0 mm ² /s ASTM D7042
Viscosity at 100 °C	12,0 mm ² /s ASTM D7042
Viscosity at -35 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -30 °C (CCS)	≤ 6600 mPas ASTM D5293
Viscosity index	165 DIN ISO 2909
High temperature/high shear viscosity	≥ 3,5 ASTM D5481
Pour point	-39 °C DIN ISO 3016



Technical data

Evaporation loss (Noack)	9,5 % CEC L-40-A-93
Flash point	230 °C DIN ISO 2592
Total base number	11,0 mg KOH/g DIN ISO 3771
Sulfate ash	1,0 - 1,6 g/100g DIN 51575
Color number (ASTM)	L 3,5 DIN ISO 2049

Areas of application

Liqui Moly Special Tec LL 5W-30 is mainly required for different Opel vehicle models and types in gasoline and diesel vehicles up to model year 2010. Backwards compatible, enabling use in older Opel vehicles. The motor oil can also be used for other vehicle models provided that the manufacturers' instructions are observed.

Application

Note the operating instructions of the vehicle and engine manufacturers.

Available pack sizes

1 l Canister plastic	2447 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-UK-ZH
4 l Canister plastic	2339 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
5 l Canister plastic	2448 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-UK-ZH
20 l Canister plastic	1194 DE-EN-ES-IT-PT
20 l Canister plastic	20928 JA

Product information

Special Tec LL 5W-30

PI 66/09/10/2026



Available pack sizes

20 l Bag-in-Box	21965
	AR-BG-CS-DA-EL-EN-ES-FI-FR-
	HR-HU-IT-KK-NL-NO-PL-PT-RO-
	RU-SK-SV-TR-ZH
60 l Black plate	1195
barrel	DE-EN-ES-FR-IT-PT
205 l Black	1196
plate barrel	DE-EN-ES-FR-IT-PT

Our information is based on thorough research and may be considered reliable, although not legally binding.