Product information
Marine 2T Motor Oil

PI 30/11/06/2026



Description
High-performance 2-stroke motor oil based on selected base oils and specially formulated additives. Ensures effective lubrication, high operational reliability, and excellent wear and corrosion protection, while preventing pre-ignition.

Properties
- high wear resistance
- high lubrication reliability
- prevents spontaneous ignition
- self mixing
- residue-free combustion

Specifications / Approvals
API TC • JASO FB • NMMA TC-W3®

Technical data

Viscosity at 40 °C	57 mm²/s ASTM D 7042-04
Viscosity at 100 °C	9,3 mm²/s ASTM D 7042-04
Viscosity index	145 DIN ISO 2909
Density at 15 °C	0,87 g/cm³ DIN 51757
Flash point	104 °C DIN ISO 2592
Pour point	-39 °C DIN ISO 3016
Total base number	9,8 mg KOH/g DIN ISO 3771
Sulfate ash	<0,02 g/100g DIN 51575
Color number (ASTM)	red DIN ISO 2049

Areas of application
For air and water-cooled 2-stroke marine engines with separate and premix lubrication systems. Self-mixing. Please note that the mixture ratio specified by the manufacturer must be observed.

Application
As is usual for 2-stroke motor oils for mixture and separate lubrication. Mixing ratio up to 1:100. Note the mixing ratios stipulated by the relevant engine manufacturers.

Available pack sizes

1 l Canister plastic	25019 AR-BG-CS-DA-DE-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-UK-ZH
5 l Canister plastic	25020 AR-BG-CS-DA-DE-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-UK-ZH

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com