Product information
Radiator Stop Leak

PI 69/09/28/2026



Description
Dispersion for sealing leaks in cooling water circuits of water-cooled engines. Reliably seals hairline cracks and smaller leaks. It can also be used preventively as protection after a cooling system repair. The solids dispersion is stabilized in carrier fluid.

Properties
- compatible with conventional coolants and antifreezes
- suitable for aluminum radiators
- permanently and reliably seals hairline cracks and small leaks
- no negative side effects on the water pump or heating circuit
- for preventive use

Technical data

Form	liquid
Color / appearance	white, characteristic
Flash point	> 100 °C
Density at 20 °C	1,053 g/ml
Sensitive to frost	yes
Shelf life in original sealed container	60 months

Areas of application
Used for sealing small leaks in cooling circuits of passenger cars, commercial vehicles and two-wheelers. Also suited for cooling water circuits equipped with water filters (with the exception of “low conductivity” coolants).

Comment
Store free of frost.

The treated product contains biocides as protective agents. Contains a mixture of 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1).

Application
Shake well before use. Add contents to the cold cooling system. Start up the heater. Then drive the vehicle at least 10 minutes. 150 ml is sufficient for up to 10 l of coolant.

Available pack sizes

150 ml Bottle aluminum	2505 DE-ES-PT
150 ml Bottle aluminum	3330 DE-FR-NL

Available pack sizes

150 ml Bottle aluminum	7129 AR-DZAR-EN-FR
150 ml Bottle aluminum	8347 BG-DE-PL
150 ml Bottle aluminum	8371 AR-EN-FR
150 ml Bottle aluminum	8956 EL-EN-IT
150 ml Bottle aluminum	20806 DE-EN-HR-SL-SR
150 ml Bottle aluminum	21352 DE-EN-ZH
150 ml Bottle aluminum	21510 DE-FR
150 ml Can aerosol	21765 AR-EN-ES-FR-PT

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com