

Gear-Oil Additive

Description

Contains highly concentrated MoS₂ to reduce wear in manual and differential transmissions, axle drives without integrated wet differential locks and mechanical steering systems. MoS₂ reduces temperature peaks and ensures quieter running and smoother shifting. The transmission heats up less and benefits from smoother tooth faces in terms of quieter running and improved performance.

Properties

- friction and wear reducing
- increases operational reliability
- resistant to stresses and vibrations
- assures optimum shifting performance
- outstanding emergency-running properties
- reduces transmission noise
- secures optimum transmission operation

Technical data

Color / appearance	darkgrey
Viscosity at 20 °C	330 mPas
Flash point	> 100 °C DIN ISO 2592
Form	liquid
Odor	characteristic
Density at 20 °C	0,998 g/ml
Shelf life in original sealed container	60 months

Areas of application

For manual and differential transmissions, axle drives without integrated wet differential lock and mechanical steering systems, especially under high thermal loads.

Comment

Not suitable for use on motorbikes with wet clutches!

Application

Add to the gear oil. Mixing takes place automatically during operation. Suitable for both mineral and synthetic gear oils. 20 g is sufficient for 1 liter of gear oil. 50 g is sufficient for 2.5 liters of gear oil.

Available pack sizes

20 g Tube plastic	2652 PL
20 g Tube plastic	8387 RO
20 g Tube plastic	21487 HU

Available pack sizes

50 g Tube plastic	2510 EN-ES-IT
50 g Tube plastic	21643 ES-PT



Our information is based on thorough research and may be considered reliable, although not legally binding.