

Radiator Stop Leak Plus

Description

Dispersion for sealing leaks in water-cooling systems in motor vehicles. The product reliably seals hair cracks and small leaks. The solids dispersion is stabilised in carrier fluid.

Properties

- suitable for coolant circuits with water filter
- permanently and reliably seals hairline cracks and small leaks
- no negative side effects on the water pump or heating circuit
- suitable for aluminum radiators
- compatible with conventional coolants and antifreezes



Our information is based on thorough research and may be considered reliable, although not legally binding.

Technical data

| | |
|---------------------|------------------------|
| Color / appearance | orange to brown |
| Form | liquid |
| Density at 20 °C | 1,04 g/cm ³ |
| Viscosity | n.a. |
| Solubility in water | mixable |
| Odor | characteristic |

Areas of application

Used for sealing small leaks in cooling circuits of passenger motor vehicles, commercial vehicles, buses and two-wheel vehicles.

Comment

Store free of frost.

The treated product contains biocides as protective agents. Contains a mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1).

Application

Shake well before use. Add contents to the cold cooling system. Start up the heater. Then drive the vehicle for at least 10 minutes. Contents will treat 10 liters of coolant.

Available pack sizes

| | |
|--------------------------|------------|
| 250 ml Can sheet metal | 2533 |
| | D-GB-I-E-P |
| 205 l Black plate barrel | 2534 |
| | D-GB |