# Product information

PI 52/11/20/2026

## Motorbike 4T 15W-50 Street




### Description

High-performance motor oil. Ensures maximum performance and protection of the engine under all operating conditions. Optimum lubrication, outstanding engine cleanliness, excellent friction values and minimum wear are just as much par for the course as gentle clutch engagement and disengagement and gear shifting. Tested on engines with catalytic converters.

### Properties

- outstanding engine cleanliness
- optimum stability to aging
- high wear resistance
- high shear stability
- tested for the use with catalytic converters
- especially suitable for wet clutches
- guarantees low oil consumption
- optimum lubrication under all operating conditions

### Specifications

API SP • JASO MA2

### Technical data

| | |
|---|---|
| SAE class (engine oils) | 15W-50<br>SAE J 300 |
| Density at 15 °C | 0,870 g/cm³<br>DIN 51757 |
| Viscosity at 40 °C | 140,0 mm²/s<br>ASTM D 7042-04 |
| Viscosity at 100 °C | 18,3 mm²/s<br>ASTM D 7042-04 |
| Viscosity index | 145<br>DIN ISO 2909 |
| Viscosity at -20 °C (CCS) | <= 7000 mPas<br>ASTM D5293 |
| HTHS at 150°C | ≥ 3,7 mPas<br>ASTM D 5481 |
| Pour point | -30 °C<br>DIN ISO 3016 |
| Evaporation loss (Noack) | 10,6 %<br>CEC-L-40-A-93 |
| Flash point | 230 °C<br>DIN ISO 2592 |
| Total base number | 7,0 mg KOH/g<br>DIN ISO 3771 |
| Sulfate ash | 0,8 g/100g<br>DIN 51575 |
| Color number (ASTM) | L 2,0<br>DIN ISO 2049 |
| Oil base | Advanced Full Synthetic |

### Areas of application

Developed for air and water-cooled 4-stroke engines exposed to normal to extreme operating conditions. For sporting applications. Suitable for engines with or without a wet clutch.

### Application

The operating instructions of the engine manufacturers must be followed.
**Note: Optimum effectiveness only when the product is used unmixed.**

### Available pack sizes

| | |
|---|---|
| 1 l Canister plastic | 2555<br>AR-BG-CS-DA-DE-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH |
| 1 l Canister plastic | 23228<br>AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH |
| 4 l Canister plastic | 1689<br>AR-BG-CS-DA-DE-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH |
| 4 l Canister plastic | 23229<br>AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH |
| 20 l Canister plastic | 2722<br>DE-EN-ES-FR-IT-PT |
| 60 l Black plate barrel | 2565<br>DE-EN-ES-FR-IT-PT |
| 205 l Black plate barrel | 2566<br>DE-EN-ES-FR-IT-PT |

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com