

Diesel Additive

Description

Combination of active agents with cleaning, dispersing, material-protecting, and cetane-boosting properties. Formulated for today's engines, operating fluids, and operating conditions.

Properties

- keeps injection nozzles clean
- tested for the use with catalytic converters
- high engine cleanliness
- prevents the build-up of deposits
- guarantees optimum combustion
- prevents seizing and the injector needles from gumming up
- optimizes engine performance
- boosts the cetane number

legally binding.



Technical data

Base	additive mixture in carrier fluid
Density at 15 °C	0,8297 g/cm ³
Color / appearance	yellow, orange
Flash point	63 °C
Odor	n.a.
Form	liquid
Viscosity at 40 °C	<7 mm ² /s

Areas of application

Added to diesel fuel for all diesel engines in passenger and heavy goods vehicles, tractors, construction machinery and stationary engines. Ideally suitable for preserving engines when decommissioned for long periods under extreme conditions.

Application

Add to the tank before refueling the vehicle. Sufficient for up to 60 liters of diesel fuel.

Available pack sizes

300 ml Can sheet metal	2585 DE-EN-ES-IT-PT
300 ml Can sheet metal	2643 HU-PL-RO-TR
300 ml Can sheet metal	21471 DA-EN-FI-NO-SV
300 ml Can sheet metal	23246 AUEN-EN
200 l Black plate barrel	8933 DE-EN

Our information is based on thorough research and may be considered reliable, although not