

Description

Combination of additives with cleaning, dispersing and material-protecting properties, matched to present-day engines, fuels and operating conditions.

Properties

- highly economical
- guarantees low fuel consumption
- guarantees optimum combustion
- easier cold start in winter
- prevents seizing and the injector needles from gumming up
- prevents the build-up of deposits
- protects injection pumps, injector needles and cylinder/piston

Technical data

Base	additive mixture in carrier fluid
Density at 15 °C	0,8297 g/cm ³
Color / appearance	yellow, orange
Flash point	63 °C
Odor	n.a.
Form	liquid
Viscosity at 40 °C	<7 mm ² /s

Areas of application

Added to diesel fuel for all diesel engines in cars and commercial vehicles, tractors, buses, construction machinery and stationary engines. Ideally suitable for preserving engines when decommissioned for long periods under extreme conditions.

Application

Contents of 1 l sufficient for 400 l of diesel fuel. 25 ml measuring cup (integrated in the screw cap) will treat 10 l of diesel fuel. The product mixes with the fuel automatically. For long-term application with every refueling.

Available pack sizes

1 l Can sheet metal	2663
	D-PL-BG
1 l Can sheet metal	5160
	D

Our information is based on thorough research and may be considered reliable, although not legally binding.

