Product information Tacky Lube Spray

PI 33/09/15/2023



Description

Adhesive Lubricant Spray is a high-quality, synthetic, heat-resistant, extremely adherent lubricant compound that is resistant to acceleration forces. After the solvent has evaporated, the product leaves an extremely adherent, soft film of grease.

Properties

- outstanding corrosion protection
- excellent creep properties
- highest load-carrying capacity
- high bond strength
- has a lasting effect
- good water resistance
- outstanding thermal stability

Technical data

Base	synthetic oil, mixed polymers
Color / appearance	pale yellow
Operating temperature range	-30 - +180, intermittent to +200 °C
Propellant	propane, butane
Shelf life in original sealed container	60 months

Areas of application

For the preventative regular lubrication of components in vehicles such as hinges, joints, linkages, reversing levers and door catch bands.

Application

Spray an appropriate amount of Adhesive Lubricant Spray onto the cleaned parts to be treated.

Follow the relevant instructions of the vehicle manufacturer.

Available pack sizes

400 ml Can aerosol	2518 D-GB-I-E-P
400 ml Can aerosol	2664 PL-H-RO-TR
400 ml Can aerosol	2842 GB-DK-FIN-N-S
400 ml Can aerosol	4084 D-F-NL
400 ml Can aerosol	21996 MX

Available pack sizes

400 ml Can aerosol 39016 D-RUS-UA

Our information is based on thorough research and may be considered reliable, although not legally binding.