

MoS2-Rust Solvent

Description

Excellent lubricant for all moving parts. Penetrates even the tightest fits and infiltrates and dissolves rust. Prevents squeaking noises, corrosion as well as oxidation and keeps moving parts permanently smooth-running. Penetrates quickly and is neutral to most paints, metals, plastics and elastomers. Displaces water and ensures low friction values thanks to MoS2 solid lubricant.

Properties

- dissolves rust
- releases dirt
- penetrates fast
- good corrosion protection
- low coefficient of friction
- good water resistance

Technical data

Base	combination of oils, agents and MoS2 solid
Color / appearance	grey
Spreading rate (cover)	sheet steel, bright 140-180 m ² /l
Operating temperature range	-40 bis +140 °C
Odor	characteristic
Form	aerosol, liquid

Areas of application

For a wide range of applications and devices in the factory, workshop, automotive as well as household and hobby.

Application

Spray a generous amount onto bolts or nuts to be loosened and as is usual with rust removers, allow to act for some time before loosening, depending on the corrosion formation. Repeat the process in extreme cases.

Available pack sizes

300 ml Can aerosol	1614 D-GB-I-E-P
300 ml Can aerosol	1817 D-NL-F-GR-ARAB
300 ml Can aerosol	2694 PL-H-RO-TR
600 ml Can aerosol	1613 D-GB-I-E-P
600 ml Can aerosol	2653 PL-H-RO-TR



Available pack sizes

600 ml Can aerosol 2993
GB-DK-FIN-N-S

Our information is based on thorough research and may be considered reliable, although not legally binding.