Product information
Chain Spray

PI 26/09/18/2026



Description
High-quality heat-resistant and extremely adherent lubricant compound that is resistant to acceleration forces. After the solvent has evaporated, the product leaves an extremely adherent, soft film of grease. Also suitable for O-ring chains.

Properties
- friction and wear reducing
- highest load-carrying capacity
- excellent adhesion
- outstanding corrosion protection
- resistant to acceleration forces
- reduces chain elongation
- especially cold, hot and splash-water resistant
- excellent penetration action

Technical data

Color / appearance	colourless,clear
Base	oil with adhesion improver
Operating temperature range	-30 to +180, short periods up to 200 °C
Water resistance at 90 °C	0 DIN 51 807
Form	aerosol, liquid
Odor	characteristic
Shelf life in original sealed container	60 months

Areas of application
Initial and maintenance lubrication of power-transmission chains. Especially suitable for dusty, dirty and corrosive environments. Due to extremely good adherence, especially suitable for high-load, fast-running chains.

Application
Carefully clean chain with solvent such as Rapid Cleaner. Apply by spraying. The lubricant attains its final consistency and adherence once the solvent has rapidly evaporated.

Available pack sizes

200 ml Can aerosol	2804 DA-EN-FI-NO-SV
200 ml Can aerosol	3581 DE-EN-ES-IT
400 ml Can aerosol	1813 AR-DE-EL-FR-NL

Available pack sizes

400 ml Can aerosol	3579 DE-EN-ES-IT-PT

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com