Product information

PI 2/05/16/2024

Gear Tronic III

Description

Fully automatic ATF service device for automatic transmissions. The perfect all-round solution for quickly, easily and reliably performing flushing, transmission fluid changes and the addition of additives. With modern control technology and intuitive operation using a 7" color touch display. After the integrated cleaning program is applied, ensures outstanding function again even with heavily soiled transmissions. Two independent scales offer high accuracy of the liquid exchange process. Data on the total fill quantity, type and density of the automatic transmission fluid, tightening torques of the oil pan, drain plug and checking screws and the vehicle manufacturer, vehicle type and engine can be retrieved using the free integrated database. Thanks to the WLAN function, service data can be sent directly to the printer or the workshop's e-mail address. The data can also be saved to a USB stick. Accessories included: Gear Tronic Adapter Kit Standard 01 (part no. 29021).



Areas of application

For all converter gears, continuously variable transmissions and dual clutch transmissions. Specially designed for the professional replacement of transmission fluids. Enables the change to be made via the cooler as well as the dipstick mode including cleaning. Universally suitable for use with all vehicle models.

Comment

Tank capacity: 25 l

Additive capacity: 0.5 l

Pump capacity: 10 l/min>

Outer dimensions: 1,020 x 750 x 650 mm (H x W x D)

Weight: 65 kg

Application

More detailed information about the device and its operation in our operating instructions or our application video.

Available pack sizes

1 pcs Carton	29266
	D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com