Product information

Motorbike Engine Flush Shooter



Description

A highly effective formulation for quick and safe removal of deposits from engines before an oil change. A clean engine will provide less wear, lower emissions and improved performance while preventing premature oil degradation.

Main LIQUI MOLY MOTORBIKE Engine Flash SHOOTER CAUTION COMMISSION 2.7 FL 0Z (80 mL)

and may be considered reliable, although not legally binding.

PI 45/07/04/2022

Properties

- cleaning and care
- simple to use
- does not attack common sealing materials
- restores the engine to its original performance
- long engine service life
- highly economical
- ideal with catalytic converters

Technical data

Color/appearance yellow, cloudy

Form liquid

Base additive, carrier liquid

Viscosity at 104 °F 22,58 mm²/s

Flash point 141 °F Pour point -49 °F

Odor characteristic
Density at 68 °F 0,815 g/cm³

Areas of application

Suitable for all 4-stroke engines, with or without wet clutches. Safe with catalytic converters.

Comment

▲ WARNING: Cancer - www.P65Warnings.ca.gov.

Application

Contents (80 mL) is sufficient for 0.8–2 Liters (0.2 gal. to 0.5 gal.) oil. Add contents to warm motor oil before the oil change. After adding allow the engine to idle for 10 minutes, during the application pull in and hold clutch lever multiple times for a few seconds. Then drain the oil and change the filter.

Available pack sizes

80 ml Can sheet metal 20196

USA-EN

80 ml Can sheet metal 20334

CANADA-FN-F

Our information is based on thorough research

Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de