

# Product information

## Motorbike Speed Additive

PI 42/02/17/2023



### Description

A unique, state-of-the-art combination of acceleration-enhancing, cleaning, dispersing and material-protecting additives. Easy engine start, smoother running and better throttle response are the effects.

### Properties

- higher performance gain
- improves acceleration
- cleans the fuel system
- protects fuel against oxidation and aging
- prevents corrosion in the fuel system
- prevents carburetor icing
- increases operational reliability

### Technical data

Base	additive mixture in carrier fluid
Color / appearance	yellow, clear
Odor	characteristic
Form	liquid
Viscosity at 104 °F	<7 mm <sup>2</sup> /s
Density at 68 °F	0,814 g/cm <sup>3</sup>
Hazard class as per German VbF	A III
Flash point	>61 °F

### Areas of application

Suitable for all 2- stroke and 4-stroke gasoline engines. Safe with catalytic converters.

### Comment

**⚠ WARNING:** Cancer- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

### Application

Contents (150 mL) is sufficient for 15–20 Liters (4 gal. to 5.3 gal.) gasoline. Add at every fill-up.

### Available pack sizes

150 ml Can sheet metal	20108
	USA-EN
150 ml Can sheet metal	22104
	CANADA-EN-F

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

