

Motorbike Radiator Stop Leak

Description

Dispersion for sealing leaks in cooling water circuits. The product reliably seals hairline cracks and small leaks. Can be used to prevent the need for repair work on the cooling system. The solids dispersion is stabilized in carrier fluid.

Properties

- compatible with conventional coolants and antifreezes
- permanently and reliably seals hairline cracks and small leaks
- suitable for aluminum radiators
- no harmful side effects

Technical data

Form	liquid
Color / appearance	white, cloudy
Density at 20 °C	1,05 g/cm ³
Solubility in water	mixable
Odor	weak
Flash point	>100 °C

Areas of application

For sealing minor leaks in coolant systems with and without coolant filter. Also suitable for aluminum and plastic radiators.

Comment

Store free of frost.

The treated product contains biocides as protective agents. Contains a mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1).

Application

Shake before use. Add contents to the cold cooling system. Then drive the vehicle for at least 10 minutes. Contents will treat up to 5 liters of coolant.

Available pack sizes

125 ml Bottle aluminum	3043
	DE-EN-ES

Our information is based on thorough research and may be considered reliable, although not legally binding.

