

## Brake Fluid SL6 DOT 4

### Description

Synthetic brake fluid based on glycol ethers and their boric acid esters. It also contains effective corrosion inhibitors and antioxidant additives. Specially developed to extend the operating life of components in the hydraulic brake and clutch systems of motor vehicles. The brake fluid has a high boiling point and wet boiling point, thus ensuring safe braking even after the absorption of some moisture over an extended period of use. Special moisture scavengers help to prevent against the formation of vapor bubbles.

### Properties

- outstanding thermal stability
- extremely high wet and dry boiling points
- excellent elastomer compatibility
- highest thermal stability
- outstanding protection against the formation of steam bubbles
- assures a high degree of lubricating action on all moving components in the hydraulic brake circuit
- miscible and compatible with high-quality synthetic brake fluids

### Specifications / Approvals

FMVSS 116 DOT 3 • FMVSS 116 DOT 4 • ISO 4925 Class 6 • SAE J 1703 • SAE J 1704

**LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required**

Audi 501 14 (TL 766-Z) • BMW QV 34 001 • GM Europe GMW 3356 • Seat 501 14 (TL 766-Z) • Skoda 501 14 (TL 766-Z) • VW 501 14 (TL 766-Z)

### Technical data

Density at 20 °C	1,06 - 1,07 g/cm <sup>3</sup>
Boiling point	min. 265 °C
Viscosity at -40 °C	≤ 750 mm <sup>2</sup> /s
Color / appearance	light yellow, colourless
Viscosity at 100 °C	min. 1,5 mm <sup>2</sup> /s
pH value	7 - 8 20°C SAE J 1703, SAE J 1704
Form	liquid
Odor	characteristic
Flash point	> 126 °C ISO 2592 (Cleveland, open cup)
Viscosity at 20 °C	11 - 14 mm <sup>2</sup> /s 20°C SAE J 1703, SAE J 1704



### Technical data

Shelf life in original sealed container 48 months

### Areas of application

Exceptionally well-suited for use in hydraulic brake and clutch systems in vehicles for which a synthetic brake fluid is prescribed. With its low low-temperature viscosity, this brake fluid is especially suitable for brake systems equipped with modern safety systems such as ESP/DSC, ABS and/or ASR.

Note: Note the manufacturer's instructions!

### Application

Can be used in all conventional brake fluid bleeding devices. Miscible and compatible with all high-quality synthetic brake fluids. The optimal period of use for this brake fluid is, however, only ensured when it is used alone. It is recommended that the brake fluid be changed in accordance with the specifications from the vehicle manufacturer.

Note: Brake fluid is hygroscopic and must be stored in tightly sealed containers. Reseal the container immediately after opening.

### Available pack sizes

500 ml Can sheet metal 3086  
D-GB-I

**Our information is based on thorough research and may be considered reliable, although not legally binding.**