# **Product information**

# Battery Clamp Grease Spray



### **Description**

Special grease which is compatible with plastics for the maintenance and care of vehicle electronic systems, particularly the battery terminals and electrical connectors. Ensures reliable starting and a longer battery life. Offers high corrosion protection and prevents leakage currents. Prevents the contact resistance from increasing during operation and ensures lower loss than with untreated contacts.

# **Properties**

- compatible with plastics
- prevents the contact resistance from increasing during operation and ensures lower loss than with untreated contacts
- good corrosion protection
- prevents leakage currents
- good electronic properties

#### **Technical data**

Thickener Calciumseife

NLGI number

**DIN 51818** 

Color / appearance red

Form aerosol, liquid

Dropping point for the solids **DIN ISO 2176** 

100 °C

Worked penetration 265-295

DIN 51804

-30 to +60 °C Operating temperature range

Emcor corrosion class

DIN 51802

Odor characteristic

# Areas of application

Used especially for battery terminals and connections in vehicle electronic systems.

#### Comment

After spraying on, allow a flash-off period of 10 min. before connecting the component to a power supply.

#### **Application**

Gently shake spray can before use. Clean contaminated components and treat the surface after joining the contacts.

#### Available pack sizes

300 ml Can aerosol 3141

D-GB-I-E-P

Our information is based on thorough research



and may be considered reliable, although not legally binding.

Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871 www.liqui-moly.com