

Product information

Exhaust Repair Paste

PI 33/09/15/2026



Description

For quick, easy, cost-effective repairs to exhaust systems. Highly heat-resistant, it provides a gas-tight seal for small holes and cracks in exhaust systems.

Properties

- simple to use
- high gas tightness
- outstanding thermal resistance
- no dismantling or welding work necessary
- does not contain flammable solvents
- cost-effective repairs



Technical data

Form	pastelike, solid
pH value	~ 10
Odor	odourless
Density	~ 1,92 g/cm ³
Base	inorganic materials
Thermal stability	ca. 700 °C
Color / appearance	dark grey
Solubility	insoluble
Shelf life in original sealed container	24 months

Areas of application

Used for eliminating leaks and sealing small holes and cracks in exhaust systems.

Application

Thoroughly clean dirt and rust from the parts to be treated. Allow the engine to run until the exhaust system has heated up. Moisten the place to be repaired and the Exhaust Repair Paste and press paste into the damaged area. Smooth down the moistened paste. The paste is hardened by heat radiating from the exhaust system or from the engine idling.

Available pack sizes

200 g Tube plastic	2898
	DA-EN-FI-NO-SV
200 g Tube plastic	3340
	DE-EN-ES-IT-PT

Our information is based on thorough research and may be considered reliable, although not legally binding.