Product information
Exhaust Bandage

PI 22/09/16/2026



Description
For quick, cost-effective repairs to exhaust systems. It is heat-resistant and provides a gas-tight seal for small holes and cracks in exhaust systems.

Properties
- solvent-free
- simple to use
- high gas tightness
- outstanding thermal resistance
- cost-effective repairs
- cures by heat from the exhaust
- high strength

Technical data

NLGI number	n.a.
Density	~ 1,92 g/cm³
Base	inorganic materials
Thermal stability	ca. 700 °C
Color / appearance	colourless
Form	pastelike, solid
Odor	odourless
Shelf life	approx. 1 year well sealed in its original container, stored in a cool and frost-free area
Thermal stability when dry	~ 700 °C

Areas of application
Used for eliminating leaks and sealing holes and cracks in exhaust systems.

Application
Remove any dirt and loose rust. Moisten the area around the damage. Apply LIQUI MOLY Exhaust-Repair Paste and firmly wrap glass fabric bandage around the damaged area or cut the glass fabric bandage to size and apply it. In a next step, apply LIQUI MOLY Exhaust-Repair Paste again, leave it to harden and repeat the process as necessary. Hardening is achieved thanks to the heat from the exhaust. Note: Protective gloves and goggles should be worn if necessary when working with this material.

Available pack sizes

1 m Can sheet metal	3344 DE-EN-ES-IT-PT

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com