# **Product information**

PI 18/08/16/2022

# Pro-Line Injector and Glow Plug Grease



# **Description**

Partly synthetic, metal-free special grease for lubricating injectors, spark and glow plugs before installation in the engine. Blocks the ingress of moisture and so prevents corrosion of the injector and glow plug. The special grease also makes disassembly much easier.

# **Properties**

- prevents seizing and cold welding
- especially resistant to cold and hot water
- excellent corrosion protection
- highest load-carrying capacity
- does not attack common sealing materials
- non-toxic
- resistant to certain organic acids and alkalis

#### Technical data

Color / appearance weiß/white
Density at 20 °C 1,09 g/cm³
Form paste

Thickener inorganic thickeners and

light solid lubricants

Dropping point no one

Operating temperature

range Base

synthetic oil, mineral oil

-40 to 1400 °C

Base oil viscosity 40°C 100 mm<sup>2</sup>/s

# Areas of application

For the lubrication of all kinds of high-load sliding surfaces and separating components subject to heat stress such as injectors, spark and glow plugs, pins and bolts.

# **Application**

Before being treated with the special grease, all components must be clean and free of residues, dirt and moisture. Apply to the cleaned surfaces using a paint brush, brush or lint-free cloth. Apply the amount which is appropriate for the application.

### Available pack sizes

20 g Tube plastic 3381

D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.



Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de