Product information

LM 40 Multi-Purpose Spray



Description

Combination of active agents with corrosion protection, rust removing and water displacing properties and outstanding lubricating effect. Also improves electrical conductivity at contacts and removes dirt and stubborn oil and grease residues. Keeps moving parts in all areas from seizing up. Has a pleasant coconut fragrance.

MOLY MOLY Molecular in the second region region in the second region reg

Properties

- optimum penetration properties
- dissolves rust
- good water resistance
- lubricates and maintains
- good corrosion protection
- improves electrical conductivity
- releases dirt
- friction and wear reducing
- silicone-free
- keeps moving parts from seizing up
- high load capacity
- does not attack plastics, paints, metals and wood
- universal application

Technical data

Form liquid

Base combination of oils,

agents

Color / appearance brown odor coco Density at 20 °C 0,8 g/cm 3 viscosity at 40 °C $< 7 \text{ mm}^2/\text{s}$ Operating temperature -40 to + 140 °C

range

Spreading rate (cover) sheet steel, bright

140-180 m²/l

Areas of application

The multipurpose product for house, hobby, workshop, vehicle and industry. For hinges, rollers, locks, bolts, switches, handles, Bowden cables, vehicle antennas and much more.

Application

Spray the area to be treated and leave it to take effect. Can also be sprayed upside down.

Available pack sizes

50 ml Can aerosol 3394

D-GB

Available pack sizes

200 ml Can aerosol 2815

GB-DK-FIN-N-S

200 ml Can aerosol 3390

D-GB-I-E-P

PI 42/11/13/2023

200 ml Can aerosol 8946

D-NL-F-GR-ARAB

400 ml Can aerosol 2816

GB-DK-FIN-N-S

400 ml Can aerosol 3391

D-GB-I-E-P

Our information is based on thorough research and may be considered reliable, although not legally binding.

Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de