

## Rapid Rust Solvent

### Description

Extremely fast rust solvent. Rapidly frees seized bolts and nuts. Penetrates even the narrowest of openings. Rust is penetrated and dissolved.

### Properties

- dissolves rust
- outstanding resistance to salt water
- good corrosion protection
- does not attack plastics, paints and metals
- penetrates fast
- low coefficient of friction
- releases dirt

### Technical data

Form	liquid
Base	combination of oils, agents
Color / appearance	brown
Odor	characteristic
Density at 20 °C	0,84 g/cm <sup>3</sup>
Viscosity at 40 °C	< 7 mm <sup>2</sup> /s
Flash point	62 °C
Solubility in water	soluble
Operating temperature range	- 40°C to + 140°C °C
Spreading rate (cover)	sheet steel, bright 140-180 m <sup>2</sup> /l
Base	combination of oils, agents
Color / appearance	brown
Density at 20 °C	0,84 g/ml DIN 51757
Operating temperature range	-40 bis +140 °C
Form	liquid
Odor	characteristic

### Areas of application

The outstanding characteristics of EPRO Rust Solvent allow the product to be used in a wide variety of applications in operations, in the workshop, on motorized vehicles and on all household and hobby appliances.

### Application

Spray with the air spray can or spray gun or apply by immersion, brush or wiping.

### Available pack sizes



### Available pack sizes

5 l Canister plastic	3611 D-GB
50 l Black plate barrel	3612 D-GB

**Our information is based on thorough research and may be considered reliable, although not legally binding.**