Product information

PI 2/10/15/2021

Top Tec ATF 1900



Description

Top Tec ATF 1900 is one of the new generation of high-performance oil for automatic transmissions. It is based on selected basic oils and modern, high-performance additives. The low viscosity helps to reduce the fuel consumption and increases the efficiency. The excellent stability of the friction coefficient enables extended oil change intervals.

Properties

- riduce il consumo di carburante
- buon rapporto viscosità-temperatura
- eccellente comportamento all'attrito
- alto rendimento
- ottime caratteristiche alle basse temperature

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

MB 236.15

Technical data

Densità a 15 °C	0,845 g/cm³ DIN 51757
Viscosità a 40 °C	19 mm²/s ASTM D 7042-04
Viscosità a 100 °C	4,4 mm²/s ASTM D 7042-04
Viscosità a -40 °C (Brookfield)	<= 10000 mPas ASTM D 2983-09
Indice di viscosità	148 DIN ISO 2909
Punto di scorrimento	-51 °C DIN ISO 3016
Punto di infiammabilità	190 °C DIN ISO 2592
Colore/aspetto	blaugrün

Areas of application

Developed for Mercedes-Benz 7-speed automatic transmissions of type 722.9 and 724.2 (hybrid).

Application

The specifications and instructions from the assembly or vehicle manufacturer must be followed! Do not mix with oils which have other specifications!

Available pack sizes

1 l Barattolo plastica	3648 D-GB-I-E-P
20 l Tanica plastica	3649 D-GB-I-E-P
60 l Fusto lamiera	20615 D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com