### **Product information**

## Top Tec ATF 1600

# PI 35/02/28/2024 LIQUI

#### **Description**

The next generation of high-performance automatic transmission fluid based on synthetic technology and modern, powerful additive components. In addition to the outstanding stability against aging and oxidation, ideal shifting under all operating conditions is guaranteed thanks to the extremely high viscosity index. Developed specifically for automatic transmissions that are installed in various Mercedes-Benz vehicles and also used to eliminate shifting problems.

#### **Properties**

- excellent corrosion protection
- excellent wear resistance
- prevents foam formation
- excellent viscosity/temperature properties
- very good low-temperature properties
- outstanding resistance to oxidation
- for eliminating shifting problems
- outstanding friction characteristics
- excellent resistance to aging

#### **Specifications / Approvals**

MB-Approval 236.14

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

MB 236.12

#### **Technical data**

Density at 15 °C 0,85 g/cm<sup>3</sup>

DIN 51757

Viscosity at 40 °C 28,7 mm<sup>2</sup>/s

ASTM D 7042-04

Viscosity at 100 °C 6,45 mm<sup>2</sup>/s

ASTM D 7042-04

Viscosity at -40 °C (Brookfield) <= 20000 mPas

ASTM D 2983-09

Viscosity index 188

DIN ISO 2909

Flash point 206 °C

**DIN ISO 2592** 

Pour point -45 °C

**DIN ISO 3016** 

Color / appearance rot

#### Areas of application

Developed for the latest generation of the Mercedes Benz 7-speed automatic transmission and is backwards compatible with the older Mercedes-Benz



5-speed automatic transmissions. Transfer boxes also sometimes require a lubricant with this specification. Usage according to the prescribed specifications from the unit or vehicle manufacturer.

#### **Application**

Shake well before use. The specifications and instructions from the assembly or vehicle manufacturer must be followed. Optimum effect only when the product is used unmixed.

#### Available pack sizes

1 l Can plastic 3659

D-GB-I-E-P

1 l Can plastic 3670

D-NL-F-GR-ARAB

1 l Can plastic 21235

ALGERIEN-GB-ARAB-F

5 l Canister plastic 21176

D-GB-I-E-P

20 l Canister plastic 3694

D-GB-I-E-P

60 l Black plate barrel 3696

D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.

Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de