

# Description

LIQUI MOLY central hydraulic system oils meet the highest technical requirements and are suitable for a wide range of automotive applications. The carefully selected formulations made from the best raw materials ensure excellent temperature properties and guarantee the full function of the systems even at the lowest temperatures of up to -45 °C. All central hydraulic system oils are impressive thanks to excellent wear, aging and corrosion protection as well as optimum friction values and minimal foaming tendency.

## **Properties**

- excellent viscosity/temperature properties
- very good low-temperature properties
- excellent corrosion protection
- outstanding resistance to oxidation
- high wear resistance
- optimum stability to aging

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required MB 343.0

#### **Technical data**

Density at 15 °C	0,865 g/cm³ DIN 51757
Viscosity at 40 °C	16,3 mm²/s DIN 51562
Viscosity at 100 °C	4,35 mm²/s DIN 51562
Viscosity at -40 °C (Brookfield)	≤ 20000 mPas ASTM D 2983-09
Viscosity index	191 DIN ISO 2909
Pour point	-51 °C DIN ISO 3016
Flash point	160 °C DIN ISO 2592
Color number (ASTM)	L 1,0

## **Areas of application**

This mineral hydraulic fluid is specially adapted to the requirements of Mercedes-Benz and is suitable for systems such as level controls, hydropneumatic suspensions, and ASD, 4Matic and soft top hydraulic systems.



### Application

Shake well before use. The specifications and instructions from the assembly or vehicle manufacturer must be followed. This oil can also be used for refilling in systems. Optimum effect only when the product is used unmixed.

#### Available pack sizes

1 l Can plastic 3665 D-GB-I-E-P

Our information is based on thorough research and may be considered reliable, although not legally binding.