

## Speed Tec Gasoline

### Description

A state-of-the-art, ash-free fuel additive for improving combustion and acceleration in partial load range. Compatible with all gasoline and additive qualities. Improves considerably vehicle acceleration.

### Properties

- improves acceleration
- optimizes engine performance
- contains no organometallic compounds
- tested for the use with catalytic converters
- does not influence the octane number
- better drivability

### Technical data

Base	Additive mixture in carrier fluid
Color / appearance	light brown
Density at 15 °C	0,825 g/cm <sup>3</sup>
Flash point	>63 °C
Odor	characteristic
Form	liquid
Viscosity at 40 °C	<7 mm <sup>2</sup> /s

### Areas of application

Used as an additive in the fuel of all 2-stroke and 4-stroke gasoline engines, especially for motor vehicle engines. Also can be used in two-wheeled vehicles. For the improvement of vehicle acceleration and smooth operation.

### Application

One 250 ml can is sufficient for max. 70 liters of gasoline fuel. Mix the contents of the can with the gasoline fuel. Mixing also takes place automatically.

### Available pack sizes

250 ml Can sheet metal	21644
	D-E-P
250 ml Can sheet metal	2848
	GB-DK-FIN-N-S
250 ml Can sheet metal	20878
	JP
250 ml Can sheet metal	3720
	D-GB-I

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

