Product information
Bio Diesel Additive

PI 31/10/01/2026



Description
Combination of active agents with cleaning, dispersing, and material-protecting properties for use with biodiesel fuel. Formulated for today's engines and operating conditions. Improves ignition performance for better fuel combustion during cold operation.

Properties
- keeps injection nozzles clean
- good corrosion protection
- tested for the use with catalytic converters
- prevents seizing and the injector needles from gumming up
- stabilizes biofuel

Technical data

Base	additive mixture in carrier fluid
Color / appearance	light brown, clear
Density at 15 °C	0,826 g/cm³
Flash point	63 °C
Pour point	-35 °C
Viscosity at 40 °C	<7 mm²/s
Odor	characteristic
Form	liquid

Areas of application
Added to biodiesel fuel for all diesel engines, particularly in modern high-pressure diesel engines in cars, trucks, tractors, construction machinery and stationary engines. Ideally suitable for preserving engines when decommissioned for long periods under extreme conditions.

Application
For continuous additive treatment to improve ignition performance, one 250 mL can is sufficient for 70 liters of diesel fuel. Dosage: 1:280.

To keep the injectors clean and protect against corrosion, add Biodiesel Additive to the passenger vehicle diesel fuel tank every 2,000 km.

When shutting down and preserving engines, add Biodiesel Additive to the biodiesel fuel at a concentration of 1%. Follow the preservation instructions.

Can be added to the fuel at any time. The product mixes with the fuel automatically.
One 250 mL can is sufficient for up to 70 liters of fuel.

Available pack sizes

250 ml Can sheet metal	3725 DE-EN-ES-IT
1 l Can sheet metal	1812 AR-DE-EL-FR-NL

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com