Product information

Top Tec 4310 0 W-30

PI 45/10/12/2026

Description

Sophisticated, low-ash low-friction motor oil for year-round use. A combination of synthetic technology and innovative additives provides excellent wear protection, reduces oil consumption, and ensures rapid oil circulation throughout the engine. Various vehicle manufacturers require a motor oil with this specification for use with diesel particulate filters (DPF) to ensure the maximum service life of the DPF.



Properties

- miscible with all commercially available motor oils
- outstanding engine cleanliness
- suitable for diesel particulate filters
- smooth engine running
- excellent corrosion protection
- rapid oil penetration
- excellent high-pressure and wear protection properties
- excellent shear stability

Specifications / Approvals

ACEA C2 • API SQ • Peugeot Citroen (PSA) B71 2312

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:

Fiat 9.55535-DS1 • Fiat 9.55535-GS1 • Peugeot Citroen (PSA) B71 2302

Technical data

SAE class (engine oils)	0W-30 SAE J300
Density at 15 °C	0,845 g/cm³ DIN 51757
Viscosity at 40 °C	51,0 mm²/s ASTM D7042
Viscosity at 100 °C	9,7 mm²/s ASTM D7042
Viscosity at -40 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -35 °C (CCS)	⩽ 6200 mPas ASTM D5293
Viscosity index	175 DIN ISO 2909
HTHS at 150°C	⩾ 2,9 mPas ASTM D5481
Pour point	-42 °C DIN ISO 3016
Evaporation loss (Noack)	10,9 % CEC-L-40-A-93

Technical data

Flash point	230 °C DIN ISO 2592
Total base number	10,5 mg KOH/g DIN ISO 3771
Sulfate ash	⩽ 0,8 g/100g DIN 51575
Color number (ASTM)	L 4,5 DIN ISO 2049

Areas of application

Ideal for the latest diesel and gasoline engines with and without multi-valve technology, turbocharging, charge air cooling and diesel particulate filter (DPF). In addition to various vehicles from PSA as well as Fiat, Alfa Romeo (TwinAir and MultiAir engines), can also in vehicles from other manufacturers that require a motor oil with this specification. Outstanding suitability for use in gas-driven passenger cars (CNG/LPG).

Application

The specifications and instructions from the assembly or vehicle manufacturer must be followed.

Available pack sizes

1 l Canister plastic	2361 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-UK-ZH
5 l Canister plastic	2362 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-UK-ZH
20 l Canister plastic	3737 DE-EN-ES-IT-PT
20 l Bag-in-Box	21843 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
60 l Black plate barrel	3738 DE-EN-ES-FR-IT-PT
205 l Black plate barrel	3739 DE-EN-ES-FR-IT-PT

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com

Product information

Top Tec 4310 0 W-30

PI 45/10/12/2026

Available pack sizes

1.000 l	21582
Container	DE-EN

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com