Product information

PI 32/04/05/2024

Fully Synthetic Hypoid Gear Oil (GL5) LS SAE 75W-140





Description

Fully synthetic hypoid gear oil, developed for use in final drives with or without wet clutch-based differentials (Limited Slip). Stable viscosity and multifunctional EP additives guarantee maximum wear protection even under extreme operating conditions. Exceeds the high requirements of well-known vehicle manufacturers and recommended for any hi-load transmission or differential in race and track vehicles or whenever added protection is needed.

Properties

- excellent viscosity/temperature properties
- reduces running noise
- outstanding corrosion protection
- excellent wear resistance
- very compatible with seals
- high pressure-absorption capability
- for extended oil-change intervals
- excellent resistance to aging

Specifications / Approvals

API GL5

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

BMW rear-axle gear oil • Ford WSL-M2C 192-A • Scania STO 1:0 • VME • ZF TE-ML 05D • ZF TE-ML 12D • ZF TE-ML 16G • ZF TE-ML 21D

Technical data

SAE class (gear oils) 75W-140

SAE J306

Density at 59 °F 0,875 g/cm³

DIN 51757

Viscosity at 104 °F 179 mm²/s

ASTM D 7042-04

Viscosity at 212°F 25 mm²/s

ASTM D 7042-04

Viscosity at -40 °F (Brookfield) <= 150000 mPas

ASTM D 2983-09

Viscosity index 172

DIN ISO 2909

Pour point -59 °F

DIN ISO 3016

Flash point 406 °F

DIN ISO 2592

Technical data

Color number (ASTM) L 1,5
DIN ISO 2049

Areas of application

Universal use in high-performance gearboxes, hypoid axles and differentials with and without an integrated differential lock system (wet clutch), particularly suitable for numerous BMW vehicles as well as for transmissions from other manufacturers where a gear oil meeting product specification is required or recommended.

Application

Observe the manufacturers instructions!

Available pack sizes

1 l Can plastic 20042

USA-EN

1 l Can plastic 22178

CANADA-EN-F

Our information is based on thorough research and may be considered reliable, although not legally binding.

Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de