Product information

PI 36/02/11/2026

Viscous Grease ZS K00K-40



Description

Lithium soap grease manufactured from carefully selected raw materials and additives. An impressive product with optimum lubricity, water resistance, adhesion and high pressure resistance. Labeling according to DIN 51502 K00K-40.

Properties

- good water resistance
- outstanding lubricating action
- excellent adhesion
- minimizes wear

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:

DTFR 33B100 (264.0) • MAN 283 Li • Willy Vogel

Technical data

Brief description	K00/000K-40 DIN 51502
Operating temperature range	-40 bis +120
NLGI number	00/000 DIN 51818
Thickener	Lithiumseife
Worked penetration	400-460 1/10 mm DIN ISO 2137
Dropping point	165 °C DIN ISO 2176
Color / appearance	grün
Flow pressure at -40 °C	<1400 mbar DIN 51805
Emcor corrosion class	0/0 DIN 51802
Copper corosion after 24 hours at 100 °C	1 b DIN 51811
Behavior in the presence of water	1-90 DIN 51807 Teil 1
Base oil	Mineralöl
Viscosity at 40 °C	45,0 mm²/s ASTM D 7042-04
Flash point	184 °C DIN ISO 2592
Pour point	-36 °C DIN ISO 3016

Areas of application

Especially suitable for central lubrication systems in trucks. As usual for flow greases, follow the operating instructions of the transmission and bearing manufacturers.

Application

Use as usual for flow greases. The operating instructions of the transmission and bearing manufacturers must be followed. Recommended for central lubrication systems in trucks.

Available pack sizes

5 kg Bucket plastic	4714 DE-EN
25 kg Bucket plastic	4715 DE-EN

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com