

Product information

megol Motorenoel Power Synt SAE 10W-40



Description

Premium low-friction motor oil. Its combination of high-tech fluids, modern additive technology and synthetic components allows it to be used year-round in gasoline and diesel engines with and without turbochargers. Improves engine performance, reduces friction and wear and lowers fuel consumption. To ensure full performance, avoid mixing with other motor oils.

Range of applications: Passenger cars.

SAPS level: High-SAPS.

Note the manufacturer's instructions!

Approvals

ACEA A3 • ACEA B4 • API CF • API SN

Meguin also recommends this product for vehicles that are subject to the following specifications

MB 229.3 • VW 502 00 • VW 505 00

Characteristic data

SAE class (engine oils)	10W-40 SAE J300
Density at 15 °C	0,865 g/cm ³ DIN 51757
Viscosity at 40 °C	91 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	14 mm ² /s ASTM D 7042-04
Viscosity at -30 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -25 °C (CCS)	<= 7000 mPas ASTM D5293
Viscosity index	158 DIN ISO 2909
HTHS at 150°C	>= 3,5 mPas ASTM D5481
Pour point	-39 °C DIN ISO 3016
Evaporation loss (Noack)	9,7 % CEC-L-40-A-93
Flash point	234 °C DIN ISO 2592
Total base number	8,2 mg KOH/g DIN ISO 3771
Sulfate ash	1,0 - 1,6 g/100g DIN 51575

Characteristic data

Color number (ASTM)	L4,0
	DIN ISO 2049

Available pack sizes

1 l Canister plastic	4804 D-GB-F-ARAB-RUS-RO-I-E-P
4 l Canister plastic	4364 D-GB-F-RUS-GR-ARAB
5 l Canister plastic	4800 D-GB-F-ARAB-RUS-RO-I-E-P
20 l Canister plastic	4805 D-GB
60 l Drum sheet metal	4806 D-GB
200 l Drum sheet metal	4807 D-GB