Product information

PI 2/05/22/2026

Formula A 10W-40



Description

High-performance low-friction motor oil with modern wear-protection technology. Prevents the formation of sludge, provides for a stable lubricating film even under extreme operating conditions, keeps oil consumption low and ensures moderate fuel consumption.

Properties

- high shear stability
- tested for turbochargers and catalytic converters
- good ageing stability
- high wear resistance
- guarantees low fuel consumption
- good cold-start behavior
- suitable for gasoline and diesel engines with and without exhaust-gas turbocharging
- prevents black sludge
- low evaporation loss
- good cleaning action

Specifications / Approvals

ACEA E7 • ACEA E9 • API CK-4 • API SP

Areas of application

For year-round use in gasoline, diesel and hybrid vehicles with and without turbocharging. Tested on engines with catalytic converters.

Application

The specifications and instructions from the assembly or vehicle manufacturer must be followed. Optimum effect only when the product is used unmixed.

Available pack sizes

5 l Canister plastic	48403
	AUEN-EN

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com