

Description

Gasoline System Treatment is a highly effective combination of agents for treating and protecting all gasoline injection systems. The agents primarily contribute to protecting all the components of the fuel system from corrosion and wear as well as treating them to prevent the formation of deposits.

Properties

- reduces residue
- prevents corrosion in the fuel system
- assures an optimum mixture
- guarantees consistently good engine performance
- guarantees low pollutant emissions
- increases operational reliability
- highly economical
- guarantees low fuel consumption
- minimizes wear
- tested for the use with catalytic converters

Technical data

Base	agents, carrier fluid
Color / appearance	light yellow
Density at 15 °C	0,804 g/cm ³
Regulation on Flammable Liquids Class (Germany)	A III
Flash point	63 °C
Viscosity at 40 °C	<7 mm ² /s
Form	liquid
Odor	characteristic

Areas of application

Used for gasoline injection systems with or without turbocharging.

Application

For preventive maintenance, add to the fuel tank every 2,000 km. The product mixes with the fuel automatically. The contents of one 300 ml can is sufficient for up to 75 litres of fuel.

With a long-term effect lasting around 2,000 km

Available pack sizes

300 ml Can sheet metal	8365
	GB-ARAB-F
300 ml Can sheet metal	5108
	D-F-NL

Our information is based on thorough research and may be considered reliable, although not legally binding.

