

Diesel Smoke Stop

Description

Contains an iron-based catalyst that helps promote more efficient combustion. Its active ingredient optimizes the combustion process in diesel engines and helps ensure more complete combustion of the fuel.

Properties

- eliminates diesel knocking
- keeps injection nozzles clean
- good corrosion protection
- high engine cleanliness
- no smell
- improves the turbidity value
- reduces soot emissions
- does not contain heavy metals
- self mixing
- prevents seizing and cold welding

Technical data

Shelf life in original sealed container	36 months
Mineral oil content	92,5 %
Color / appearance	dark brown
Odor	characteristic
Density at 20 °C	0,7956 g/cm ³
Flash point	>63 °C

Areas of application

For all passenger and commercial vehicle diesel engines without diesel particulate filter as well as stationary diesel engines. Suitable for HVO and XTL diesel fuels.

Comment

Do not combine with our Diesel Particulate Filter Protector or Diesel Smoke Stop (C).

Application

150 ml is sufficient for 100 L of diesel fuel, i.e., a 1:667 ratio. Add the contents of the can directly to the fuel tank before refueling. For the optimum effect, add every time you refuel.

Available pack sizes

150 ml Can sheet metal	1808 EL-EN-IT
150 ml Can sheet metal	2703 DE-ES-PT
150 ml Can sheet metal	5180 DE-FR-NL

Available pack sizes

150 ml Can sheet metal	8340 BG-DE-PL
150 ml Can sheet metal	8363 AR-EN-FR
150 ml Can sheet metal	20877 JA
150 ml Can sheet metal	21507 DE-FR

Our information is based on thorough research and may be considered reliable, although not legally binding.

