

Pro-Line Radiator Cleaner

Description

A concentrate specially developed for cooling systems in general but particularly those in motor vehicles. Dissolves contaminants containing oil and lime in radiators, heating systems, lines and engines. Innovative formula containing complexing agents with active cleaning agents.

Properties

- disperses sludge
- compatible with antifreeze
- good material compatibility
- neutralizes acids
- chemical conversion of lime
- neutral behavior on rubber and plastics
- does not contain acids or alkali
- removes oil and grease-based contaminants

Technical data

Form	liquid
Color / appearance	white, light unclear
Hazard class as per German VbF	none
pH value	~8,7
Solubility in water	soluble
Odor	characteristic
Density at 20 °C	1,015 g/cm ³

Areas of application

Suitable for all coolant circuits in passenger cars, buses and trucks.

Comment

Store free of frost.

Contains biocides as protective agents. Contains a mixture of 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1).

Application

Add contents to the coolant and start up the heater. Depending on the level of contamination, run the engine at operating temperature for 10 – 30 minutes. Drain the cleaner, thoroughly flush out the cooling system with water and fill according to the manufacturer's specifications. Contents will treat up to 50 liters of coolant.

Available pack sizes

1 l Can sheet metal 20455
D-PL-BG

Available pack sizes

1 l Can sheet metal 5189
D-GB-I-E-P

Our information is based on thorough research and may be considered reliable, although not legally binding.

