Product information
Pro-Line Visco-Plus

PI 23/10/09/2026



Description
Modern, mono-functional high-performance additive for stabilizing the viscosity of motor oils. Offers outstanding protection against mechanical and therefore permanent shear losses to the oil under extreme running conditions and is effective against the thinning of motor oils due to frequent cold starts. Ensures optimal lubricating film stability under all operating conditions and reduces wear. Pro-Line Visco Stable lowers oil consumption, reduces noise levels of hydraulic tappets and optimizes the engine performance of older vehicles. Does not increase viscosity in cold motor oils, ensuring good starting performance even at low temperatures.

Properties
- excellent low temperature behavior
- excellent viscosity/temperature properties
- outstanding oil film strength
- miscible with all commercially available motor oils
- minimizes wear
- long engine service life
- improves the movable seal between piston and cylinder
- reduces oil consumption
- dampens hydraulic tappet noise

Technical data

Color / appearance	orange clear
Density at 20 °C	0,89 g/cm³ DIN 51757
Viscosity at 40 °C	299,6 mm²/s ASTM D7042
Flash point	120 °C DIN ISO 2592
Pour point	-15 °C DIN ISO 3016
Odor	characteristic
Form	liquid

Areas of application
For all gasoline and diesel engines in cars, commercial vehicles, buses, construction machinery and agricultural vehicles.

Application
Contents sufficient to treat up to 20 liters of motor oil. After adding to the motor oil, allow the engine to run warm. The product can be added at any time. Do not exceed the maximum oil fill level (drain oil off before filling if necessary).
Note: Not suitable for use in vehicles with wet clutches!

Available pack sizes

1 l Can sheet metal	5196 DE-EN-ES-IT-PT

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com