Product information

Bike LM 40 Multi-Purpose Spray

PI 28/09/13/2023 LIQUI

Description

Universal combination of active constituents with excellent, corrosion-protecting, water-repelling, rust and dirt dissolving properties, as well as excellent lubricating effect. Excellent creep characteristics ensure penetration into even the tightest intermediate spaces. Reliably eliminates squeaking.

HOUND HE WAS A STATE OF THE STA

Properties

- optimum penetration properties
- good corrosion protection
- releases dirt
- eliminates squeaks
- silicone-free
- high load capacity
- universal application

Technical data

Form liquid

Base combination of oils,

agents

Color / appearance brown

Odor coco

Density at 20 °C 0,8 g/cm³

Viscosity at 40 °C < 7 mm²/s

Flash point 62 °C

Operating temperature

range

Spreading rate (cover) sheet steel, bright

140-180 m²/l

- 40 to + 140 °C

Areas of application

The excellent and versatile properties provide a wide range of applications for bikes.

Comment

Avoid contact with brakes!

Application

Apply thinly and evenly onto the previously cleaned and dried surface. Provides a visible protective film.

Available pack sizes

50 ml Can aerosol 6057

D-GB

Our information is based on thorough research and may be considered reliable, although not

legally binding.

Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de Technical hotline: +49 (0)731/1420-871 www.liqui-moly.com