

# Liquimate 8300 Seam Sealant gray

## Description

High-grade, 1-component, MS polymer-based, sprayable seam sealant. Free of isocyanate and silicone. Resistant to UV and mineral oils. With most commercially available paints, can be painted over wet-on-wet immediately (max. up to 2 hours).

## Properties

- waterproof
- can be used without primer
- permanently elastic after curing
- can be applied as a spray or with a brush
- does not contain solvent, isocyanate or silicones
- outstanding rigidity
- broad adhesive spectrum
- high resistance to aging
- resistant to mineral oils
- can be painted over wet-in-wet
- professional repairs
- easy to use

## Technical data

Base	MS-Polymer
Form	pastelike
Color / appearance	grey
Density at 20 °C	1,4 g/cm <sup>3</sup>
Curing rate at 23 °C / 50 % rh	3 mm/24 h DIN 50 015
Skin formation time at 23 °C/50 % relative humidity	20 min DIN 50 015
Elongation at break	250 %
Hardness, Shore A	47 DIN 53 505
Processing temperature	5-30 °C
Curing system	cured by moisture in the air
Thermal stability	-40-80 °C
Thermal stability, short-term (up to 1 hour)	120 °C
Recommended storage temperature	5-25 °C
Shelf life in original sealed container	18 months

## Areas of application

For sealing seams during repairs to restore to original factory condition. Areas of application include the engine compartment, trunk and wheel housings.

## Application

Surfaces must be clean and free of grease. Can be painted over after application of the material with solvent- and water-based paints. It is recommended that you check the adhesion and compatibility with plastics and paints for the specific object.

## Available pack sizes

310 ml Cartridge plastic 6150  
D-GB-F-I-E-NL-P

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

