

Cable Grease

Description

High-quality lubricant for the preservation of wire cables. Thanks to its excellent corrosion protection, it is also suitable for cavity sealing and underbody protection in the automotive sector.

Properties

- outstanding corrosion protection
- low aromatic
- highest load-carrying capacity
- high bond strength
- optimum effectiveness when the product is used unmixed
- excellent creep properties
- drives out moisture
- has a lasting effect

Technical data

Run time at 25 °C	29,5 ± 2,5 s
Density at 15 °C	0,85 ± 0,03 g/cm ³
Base	Mineral oils, wax, polymers
Color / appearance	brown
Flash point	> 61 °C
Dropping point	> 75 °C
Viscosity at 40 °C	20,5 mm ² /s
Odor	characteristic
Form	liquid, viscous
Shelf life in original sealed container	30 Monate
Recommended storage temperature	10 - 30 °C

Areas of application

For preventive preservation of wire cables. Also suitable for the cavity sealing and underfloor protection of vehicles.

Comment

Shake small packaging before using. Stir big packaging before using.

Application

Application by means of Cavity Compressed-Air Can Gun (part no. 6226) or as underfloor protection with Spray Gun (part no. 6219) or Compressed Air Can Gun (part no. 6220). An adherent film is formed after the solvent evaporates. The respective manufacturer's instructions must be observed. Optimum creep effect at an application temperature of +25 °C



Available pack sizes

1 l Can sheet metal	6173
	D-GB-I-E-P
5 l Can sheet metal	6124
	D-GB-I-E-P
60 l Drum sheet metal	6175
	D

Our information is based on thorough research and may be considered reliable, although not legally binding.