## PI 20/01/11/2024

# Product information

# DPF Pressurized Tank Spray Gun



## **Description**

The Spray-Gun is powder coated for protection and equipped with a non-return pressure valve. It comes supplied with a European style hose coupling. Reservoir size is 1 liter (34 FL OZ). The built-in manual flow valve allows precise control of spray volume. The Liqui Moly spray gun design provides a finely atomized spray pattern for a more efficient DPF cleaning.

# LIQUI MOLY

#### Technical data

Operating pressure 2-8 bar Maximum pressure 8 bar

required air quality filtered, free of condensate

## Areas of application

Designed for use together with Liqui Moly DPF-Probe (LM7945) and when applying Pro-Line Diesel Particulate Filter Cleaner and Pro-Line Diesel Particulate Filter Purge. Operating air pressure is 6-8 bar (90 - 120 psi).

#### Comment

CAUTION: Always depressurize and drain after each use and before storing.

#### **Application**

Designed for use together with Liqui Moly DPF-Probe (LM7945) and when applying Pro-Line Diesel Particulate Filter Cleaner and Pro-Line Diesel Particulate Filter Purge.

#### Available pack sizes

1 pcs Carton 7946

ח

Our information is based on thorough research and may be considered reliable, although not legally binding.

Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de