

Description

Highly effective combination of agents for treating and protecting all gasoline injection systems. The agents primarily contribute to protecting all the components of the fuel system from corrosion and wear as well as treating them to prevent the formation of deposits.

Properties

- increases operational reliability
- tested for the use with catalytic converters
- reduces residue
- prevents corrosion in the fuel system
- assures an optimum mixture
- guarantees consistently good engine performance
- minimizes wear

Technical data

Base	additive mixture in liquid carrier
Color / appearance	yellowish, light orange
Regulation on Flammable Liquids Class (Germany)	A III
Flash point	> 61 °C
Pour point	< -60 °C
Form	liquid
Odor	aromatic
Viscosity at 40 °C	<7 mm²/s
Density at 15 °C	0,808 g/ml

Areas of application

Used for gasoline injection systems with or without turbocharging.

Application

For preventive maintenance, add to the fuel tank every 2000 km. The product mixes with the fuel automatically. The contents of one 300 ml can are sufficient for up to 75 liters of fuel.

With a long-term effect lasting around 2,000 km

Available pack sizes

300 ml Can sheet metal	5108 DE-FR-NL
300 ml Can sheet metal	8365 AR-EN-FR

Our information is based on thorough research and may be considered reliable, although not legally binding.

