Product information

PI 52/11/09/2026

Molygen New Generation 5W-20



Description

High-performance, low-friction motor oil for year-round use. Unconventional base oils combined with innovative additive technology and the special Molygen additive produce a low-viscosity, highly shear-stable motor oil that reliably prevents deposits and reduces engine friction losses while providing optimal wear protection. This results in a longer engine life.

Properties

- smooth engine running
- tested for turbochargers and catalytic converters
- outstanding engine cleanliness
- miscible with all commercially available motor oils
- optimum stability to aging
- optimum oil pressure under all operating conditions
- instant lubrication after cold start
- high lubrication reliability
- long engine service life
- excellent low temperature behavior
- excellent wear protection

Specifications / Approvals

API SQ • ILSAC GF-7A

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:

Chrysler MS-6395 • Daihatsu • Fiat 9.55535-CR1 • Ford WSS-M2C 930-A • Ford WSS-M2C 945-A • Ford WSS-M2C 945-B1 • Ford WSS-M2C 960-A1 • Ford WSS-M2C 970-A1 • GM 6094 M • GM dexos1 Gen 3 • Honda • Hyundai • Kia • Mazda • Mitsubishi • Mitsubishi Dia Queen • Nissan • Subaru • Toyota

Technical data

SAE class (engine oils)	5W-20 SAE J300
Density at 15 °C	0,850 g/cm³ DIN 51757
Viscosity at 40 °C	47,0 mm²/s ASTM D 7042-04
Viscosity at 100 °C	8,5 mm²/s ASTM D 7042-04
Viscosity at -35 °C (MRV)	< 60000 mPas ASTM D 4684
Viscosity at -30 °C (CCS)	<= 6600 mPas ASTM D 5293
Viscosity index	160 DIN ISO 2909
HTHS at 150°C	>= 2,6 mPas ASTM D 5481

Technical data

Pour point	-39 °C DIN ISO 3016
Evaporation loss (Noack)	10,5 % CEC-L-40-A-93
Flash point	230 °C DIN ISO 2592
Total base number	8,2 mg KOH/g DIN ISO 3771
Sulfate ash	< 0,8 g/100g DIN 51575
Color / appearance	green, fluorescent

Areas of application

Ideal for modern Asian and American gasoline engines with multi-valve technology and turbocharging with and without charge air cooling. For the protection and value retention of the engine during long intervals between oil changes and where there are extreme demands on the engine.

Application

The specifications and instructions from the assembly or vehicle manufacturer must be followed. Can be mixed with all commercially-available motor oils. The instructions of the vehicle-/aggregate manufacturer are to be followed!

Available pack sizes

1 l Canister plastic	8539 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-UK-ZH
4 l Canister plastic	20798 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-UK-ZH
5 l Canister plastic	8540 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-UK-ZH

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com

Product information

PI 52/11/09/2026

Molygen New Generation 5W-20

Available pack sizes

205 l Black plate barrel	20799 DE-EN-ES-FR-IT-PT

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com