

Product information

Meguin Schaloel FSE 4



Description

Low-viscosity, non-emulsifying concrete release agent for wood, chipboard and steel formwork. Apply thinly and evenly to the formwork by spraying or smearing. Guarantees clean and easy demolding, smooth surfaces with sharp-profiled edges and is economic to use.

Characteristic data

	BTM 20
Density at 15 °C	0,820 g/cm ³ DIN 51757
Viscosity at 20 °C	7,7 mm ² /s ASTM D7042
Viscosity at 40 °C	4,6 mm ² /s ASTM D7042
Viscosity at 100 °C	1,65 mm ² /s ASTM D7042
Pour point	-30 °C DIN ISO 3016
Flash point	140 °C DIN ISO 2592
Neutralization number	5,0 mg KOH/g DIN 51558 T1
Color number (ASTM)	0,5 DIN ISO 2049

Application

The performance of a release agent always depends on the formwork temperature, the method (which type of formwork is used: plastic, steel, aluminum, rough or smooth wood, raw, planed, profiled, absorbent or non-absorbent?) and of course on the concrete composition.

It can be applied either by spraying, immersing or brushing.

Available pack sizes

20 l Canister plastic	8750 D-GB
200 l Black plate barrel	6886 D-GB
1.000 l Deposit container	9652 D-GB